

Safety Data Sheet

Uzin Utz AG

UZIN PE 630

2-Component Special Primer Component B

Version: 03	revised: 09/02/06	replacement version 02: 17/03/03	page 1 of 3
-------------	-------------------	----------------------------------	-------------

1. Identification of the product and company

1.1 Product name

UZIN PE 630 2-Component Special Primer Component B.

1.2 Manufacturer

UZIN UTZ AG.
Dieselstraße 3
D-89079 Ulm
Tel.: +49 731 4097-0
Fax: +49 731 4097-110

In the UK:

UZIN Ltd., 7/8 Cholswell Court Shippon, Abingdon, OX 13 6 HW
Tel. 01235/53 41 06
Fax 01235/53 41 07

Information Services:

UZIN UTZ AG, Product Security Department: tel.: +49 731 4097-207
24-hour emergency transport information: tel.: +49 621 60 43 333
24-hour emergency medical information: tel.: +49 30 19 240

2. Composition/information on ingredients

Blend of various special cements as well as chalk and quartz sand.
Low in chromate. GISCODE ZP1.

Hazardous substances	CAS-No.	EINECS-No.	% - share	Classification*
Portland cement	65997-15-1	-	5-10	Xi R 38, 41

* For the wording of the R-phrases see section 16.

◆ 3. Hazards identification

The cement content in this product makes the following labelling required:

Xi Irritant. Contains cement.

Special hazard instructions:

R 36/38 Irritating to eyes and skin

Additional information: Low in Chromate (< 2 ppm) acc. Directive 2003/53/EC.

4. First-aid measures

After skin contact: Wash with water and soap.
After contact with eyes: Rinse thoroughly with water and consult a doctor.
After swallowing: Consult a doctor, show this label / safety data sheet..

5. Fire-fighting measures

No special measures required. Extinguishing agents should be appropriate for the location.

6. Accidental release measures

Collect together spilled material and dispose according to local and national disposal regulations. Avoid producing dust. Do not allow to disperse into water systems.

UZIN PE 630

2-Component Special Primer Component B

Version: 03	revised: 09/02/06	replacement version 02: 17/03/03	page 2 of 3
-------------	-------------------	----------------------------------	-------------

7. Handling and storage

7.1 Handling

Avoid producing dust as well as contact with eyes and skin. When mixing wear a protective dust-mask. At breaks and end of work, wash hands and apply skin cream.

7.2 Storage

Protect from water and moisture.

◆ 8. Exposure limits / personal protection

8.1 Exposure limits

Ingredients with limit values that require monitoring at the workplace:

Hazardous substances	CAS-No.	% - share	OEL (mg/m ³)
Portland cement	65997-15-1	5-10	5
Quartz	14808-60-7	25-50	0,15 mg/m ³ (dust)

8.2 Personal protection

Avoid contact with eyes and skin. When mixing wear a protective dust-mask.

Protection of hands: Use nitrile impregnated cotton-gloves.

In case of splashes or formation of dust wear safety goggles.

At breaks and end of work, wash hands and apply skin cream.

9. Physical and chemical properties

Form:	Powder
Colour:	grey
Odour:	of cement
Bulk density:	app. 1,3 g/cm ³
Solubility in water (20°C):	Sets hydraulically with water
Flash point:	not applicable
Ignition temperature:	not applicable
Explosion limits:	no risk of explosion
pH-value:	app. 12

10. Stability and reactivity

When used as stated, produces no thermal decomposition, no hazardous products of decomposition and no hazardous reactions.

◆ 11. Toxicological information

The product reacts with water and moisture to produce strong alkaline and long exposure can, therefore, lead to irritation of the skin.

Primary irritant effect:

On the skin: Irritant to skin and mucous membranes.

On the eye: Strong irritant with the danger of severe eye injury.

Sensitization: Low in chromate, therefore no sensitizing effects known.

The cured, solidified product is non-irritant.

12. Ecological information

Do not allow the product to disperse into drains, sewers or ground. Water contaminant classification (German WGK) = 1, weak water contaminant (self-classification according German VwVwS of 17/05/99).

Safety Data Sheet

UZIN PE 630

2-Component Special Primer Component B

Uzin Utz AG

Version: 03	revised: 09/02/06	replacement version 02: 17/03/03	page 3 of 3
-------------	-------------------	----------------------------------	-------------

13. Disposal considerations

Where possible, collect product residues and re-use. Do not allow to get into drains, sewers or ground. Empty, dust-free paper packaging is recyclable. Collect waste product, mix with water, allow to harden and dispose as construction waste.

14. Transport information

Not hazardous goods according to transport regulations: Road Transport (ADR/RID), Sea Transport (IMDG), Air Transport (IATA/ICAO).

15. Regulatory information

Labelling according to EU guidelines:

Code letter and hazard designation of product:

Xi Irritant. Contains cement.

Special hazard instructions:

R-Phrases:

R 36/38 Irritating to eyes and skin

S- Phrases:

S 2 keep out of reach of children

S 24/25 avoid contact with skin and eyes

S 26 In case of contact with eyes rinse immediately with plenty of water and seek medical advice

S 37 Wear suitable gloves

16. Other information

This safety data sheet corresponds with the current version of regulation 91/155/EEC.

Produced by the UZIN Product Security Department. We shall be pleased to provide further information on telephone number +49 731/4097-207.

If you require a personal consultation, e.g. in conjunction with project orders, then you will find competent advisers in our Technical Division of UZIN UK. For installation or product-related queries, please call: 01235/53 41 06

Wording of R-phrases quoted in section 2: *

R 38 Irritating to skin

R 41 Risk of serious damage to eyes

* Please note that these R-phrases refer to the **individual components** of the preparation. The classification of the preparation (product) and its relevant R-phrases are specified in section 3 and section 15, resp.

Text marked ◆ has been altered from the preceding version.

Printing date: 5/18/2007



UZIN / A brand of Uzin Utz Group

Distributed in the USA by Signature Innovations, LLC

1171 Landmeier Road / Elk Grove Village, IL 60007 / USA

Toll Free 866.554.4252 / Local 847.758.9600 / Fax 847.758.9696

www.signatureinnovations.com / sales@signaturehardwoods.com